

Araldite®

professional adhesives



Araldite® Instant 24ml Syringe

A strong, long lasting solvent-free adhesive which is water resistant and can be painted or sanded. Sets in 90 seconds.

Important

Bonds metal, wood, masonry, ceramics, glass, dry concrete, chipboard, leather, cardboard, fabric, rubber and most plastics (except polyethylene, polypropylene, Teflon®, expanded polystyrene).

Make sure surfaces are clean and free from dust, corrosion, dirt and grease.

For optimum bonding, slightly roughen surfaces with sandpaper and degrease metals with a suitable solvent.

During assembly apply light pressure to the joint until set (clamps, tape) around 4 minutes. Allow 2 hours to attain full strength before rough handling or sanding.



1 Snap off the resealable cap from between the syringe plungers and break off the end seal. Depress the plunger to dispense equal amounts of both components onto a clean disposable surface. Re-fit the cap to close the nozzle.

2 Mix thoroughly for at least 20 seconds until well mixed. Araldite® Instant remains usable for max. 90 seconds.

3 Make sure both surfaces are clean and dry. Apply to both surfaces of the joint.

4 Assemble carefully and remove any excess adhesive with a sharp blade once partially set.

How to apply

Araldite® Instant is a strong 2-component epoxy adhesive with very fast setting. Sets clear. Oil, chemical and impact resistant. High temperature resistance (-30°C to 65°C).

Do not use to repair or bond items that will contact food or drink. Not recommended for bonding rear-view mirrors to car windscreens.

Storage

Should be stored in a dry place at room temperature in the original syringe.

New

Environmentally friendly product formulation plus eco-friendly packaging for easy recycling.

Copyright © 2011 . Huntsman Advanced Materials (Switzerland) GmbH. All Rights Reserved.

Araldite® is a registered trade mark of Huntsman Corporation or an affiliate thereof in one or more, but not all countries.

www.go-araldite.com