



Technical specification bucket


JET 210 P

Jokey Euro Tainer Profi

dimensions

D1: 326,0 mm
D2: 311,0 mm
D3: 280,0 mm
H:* 331,0 mm

*Height without lid



basic data

volume to rim:

weight:

22,30 I 570,0 g

weight group: E

handle types

metal handle 46,0 g plastic handle 27,0 g

plastic handle 27,0 g
belt handle no handle +
body grip +

roller grips 3,0 g

+~	Aran	200
LUI	leran	CES

dimensions: +/- 1 mm

volume/weight: +/- 5 %

 decoration
 Digital
 IML
 offset

 height:
 220,0 mm
 293,75 mm
 240,0 mm

 width:
 924,0 mm
 935,85 mm
 910,0 mm

 median breadth:
 924,0 mm
 924,0 mm

FDET 325 P DET 325 P DET 325 PR DET 325 P lid standard shaker lid standard sealing lid stacking height two 652,0 mm 652,0 mm 0,0 mm 671,0 mm fold: each further: 320,0 mm 320,0 mm 0,0 mm 329,0 mm

logistic

Max. compression for standard lid at 20 $^{\circ}\text{C}$ on the lowest pail: 70,00 kg


pieces per pallet

bucket 320 pallet height 2,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material





QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 07.12.2020 rev. 3.0



Technical specification lid **DET 325 P**



dimensions

D1: 325,3 mm H: 14,4 mm

basic data displaced volume:: 1,00 I tolerances

> 100,0 g dimensions: +/- 1 mm weight: weight group: D volume/weight: +/- 5 %

decoration IML offset

JET2K 325 Pt

Diameter 279,00 mm 250,0 mm

JET2K 325 P

JET 160 P



JET 200 P



JET 201 P

JET 210 P




pieces per pallet

1920 pallet height 2,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material



QM / certificates

You can download our current certificates on www.jokey.com.

Date: 07.12.2020 rev. 3.0

misc.

bucket

logistic

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved

Please find further Information at www.jokey.com or via email info@jokey.com



Technical specification lid **DET 325 PR**



dimensions

D1: 325,0 mm H: 16,0 mm

basic data displaced volume:: 1,20 I tolerances

> 115,0 g +/- 1 mm weight: dimensions: weight group: volume/weight: +/- 5 %

decoration IML offset

Diameter 279,00 mm 250,0 mm

JET2K 325 P JET 160 P JET 180 P bucket









Date: 07.12.2020 rev. 3.0

JET 210 P

logistic


pieces per pallet

960 pallet height 2,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com



Technical specification lid **DET 325 P**



dimensions

D1: 325,3 mm H: 14,4 mm

basic data displaced volume:: 1,00 I tolerances

> 115,0 g dimensions: +/- 1 mm weight: weight group: G volume/weight: +/- 5 %

decoration IML offset

JET2K 325 Pt

Diameter 279,00 mm 250,0 mm



JET 160 P







JET 210 P

JET2K 325 P




pieces per pallet

960 pallet height 2,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material





QM / certificates

You can download our current certificates on www.jokey.com.

Date: 07.12.2020 rev. 3.0

misc.

bucket

logistic

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved

Please find further Information at www.jokey.com or via email info@jokey.com



Technical specification lid **FDET 325 P**



dimensions

D1: 325,0 mm H: 23,5 mm

basic data displaced volume:: 0,001 tolerances

> 140,0 g +/- 1 mm weight: dimensions: weight group: Н volume/weight: +/- 5 %

decoration IML offset

720

1,20 m


Diameter 279,00 mm 250,0 mm

JET 160 P JET 180 P JET 200 P JET 201 P JET 210 P bucket



EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material



You can download our current certificates on www.jokey.com.

Date: 07.12.2020 rev. 3.0

misc.

logistic

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

pieces per pallet

layer quantities: 8

pallet height