

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® STANDARD ULTRA RESIN

Unique Formula Identifier (UFI) : F551-7047-H00P-A76G

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy constituents

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV
Address : Grijpenlaan 18
3300 Tienen
Belgium

Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone

Emergency telephone : Berlin: 0049 30 19 24 0 & 0049 30 30 68 6 7 11
Bonn: 0049 228 19 27 0 & 0049 228 28 7 3 32 11
Erfurt: 0049 361 73 07 30
Freiburg: 0049 761 16 24 0
Göttingen: 0049 51 19 24 0 & 0049 551 38 31 80
Homburg: 0049 6841 19 24 0
Mainz: 0049 6131 19 24 0 & 0049 6131 23 24 66
München: 0049 89 19 24 0
Nürnberg: 0049 911 39 8 2 45 1
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2

H315: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 13.12.2023
1.6	18.09.2024	400001021217	Date of first issue: 20.07.2018

Print Date 10.10.2025

Eye irritation, Category 2
Skin sensitisation, Category 1
Long-term (chronic) aquatic hazard,
Category 2

H319: Causes serious eye irritation.
H317: May cause an allergic skin reaction.
H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.

Prevention:

P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.

Response:

P391	Collect spillage.
------	-------------------

Disposal:

P501	Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.
------	---

Hazardous ingredients which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE)
bisphenol A - epoxy resins, number average MW >700 - <1100

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.6 Revision Date: 18.09.2024 SDS Number: 400001021217 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.10.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 ≥ 5 % Eye Irrit. 2; H319 ≥ 5 %	≥ 70 - < 90
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE)	- - 01-2119454392-40	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	≥ 2,5 - < 10
bisphenol A - epoxy resins, number average MW >700 - <1100	25068-38-6 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	≥ 1 - < 10

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

If inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
-------	---	---

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.
-----------	---	------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	Exercise caution when using a high volume water jet as it may scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon oxides Phenolics

5.3 Advice for firefighters

Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 13.12.2023
1.6	18.09.2024	400001021217	Date of first issue: 20.07.2018

Print Date 10.10.2025

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.6 Revision Date: 18.09.2024 SDS Number: 400001021217 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.10.2025

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labeled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Storage class (TRGS 510) : 10

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silicon, amorphous	112945-52-5	AGW (Inhalable fraction)	4 mg/m ³ (Silica)	DE TRGS 900
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		MAK (measured as the alveolate fraction)	0,02 mg/m ³	DE DFG MAK
Peak-limit category: 8; II				
Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4,93 mg/m ³
	Workers	Dermal	Long-term systemic effects	0,75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m ³
	Consumers	Dermal	Long-term systemic effects	0,0893 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESINVersion
1.6Revision Date:
18.09.2024SDS Number:
400001021217Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.10.2025

	Consumers	Oral	Long-term systemic effects	0,5 mg/kg bw/day
bis(2-ethylhexyl) adipate	Workers	Inhalation	Long-term systemic effects	17,8 mg/m3
	Workers	Dermal	Long-term systemic effects	25,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,4 mg/m3
	Consumers	Dermal	Long-term systemic effects	13 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1,7 mg/kg bw/day
Silicon, amorphous	Workers	Inhalation	Long-term systemic effects	4 mg/m3
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFEDGE)	Workers	Dermal	Acute local effects	0,0083 mg/cm2
	Workers	Dermal	Long-term systemic effects	104,15 mg/kg
	Workers	Inhalation	Long-term systemic effects	29,39 mg/m3
	Consumers	Dermal	Long-term systemic effects	62,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,7 mg/m3
	Consumers	Oral	Long-term systemic effects	6,25 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l
	Sea water	0,001 mg/l
	Fresh water sediment	0,341 mg/kg dry weight (d.w.)
	Sea sediment	0,034 mg/kg dry weight (d.w.)
	Soil	0,065 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Secondary Poisoning	11 mg/kg
bis(2-ethylhexyl) adipate	Soil	0,865 mg/kg dry weight (d.w.)
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFEDGE)	Fresh water	0,003 mg/l
Remarks:Assessment Factors		
	Sea water	0 mg/l
Remarks:Assessment Factors		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.6 Revision Date: 18.09.2024 SDS Number: 400001021217 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.10.2025

	Intermittent use/release	0,0254 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	0,294 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Sea sediment	0,0294 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Soil	0,237 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Sewage treatment plant	10 mg/l
	Remarks:Assessment Factors	

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Hand protection	:	
Material	:	butyl-rubber
Break through time	:	> 8 h
Material	:	Solvent-resistant gloves (butyl-rubber)
Material	:	Nitrile rubber
Break through time	:	10 - 480 min
Material	:	Neoprene gloves
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines Equipment should conform to EN 14387
Filter type	:	Combined particulates and organic vapor type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	light cream
Odor	:	slight

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 13.12.2023
1.6	18.09.2024	400001021217	Date of first issue: 20.07.2018

Print Date 10.10.2025

Odor Threshold	:	No data is available on the product itself.
Melting point/freezing point	:	No data is available on the product itself.
Boiling point	:	No data is available on the product itself.
Flammability (solid, gas)	:	No data is available on the product itself.
Lower explosion limit / Lower flammability limit	:	No data is available on the product itself.
Upper explosion limit / Upper flammability limit	:	No data is available on the product itself.
Flash point	:	210 °C Method: Pensky-Martens closed cup
Autoignition temperature	:	No data is available on the product itself.
Decomposition temperature	:	No data is available on the product itself.
pH	:	6 Concentration: 500 g/l
Viscosity	:	No data is available on the product itself.
Solubility(ies)	:	
Water solubility	:	practically insoluble
Solubility in other solvents	:	No data is available on the product itself.
Partition coefficient: n-octanol/water	:	No data is available on the product itself.
Vapor pressure	:	0,0001 kPa
Density	:	1,15 g/cm ³ (25 °C)
Relative density	:	No data is available on the product itself.
Relative vapor density	:	No data is available on the product itself.
Particle characteristics	:	No data is available on the product itself.

9.2 Other information

No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity	:	LD50 (Rat, female): > 2 000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	:	LD50 (Rat, male and female): > 2 000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE):

Acute oral toxicity	:	LD50 (Rat, male and female): > 5 000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 (Rat, male and female): > 2 000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute oral toxicity	:	LD50 (Rat, female): > 2 000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity
---------------------	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 13.12.2023
1.6	18.09.2024	400001021217	Date of first issue: 20.07.2018

Print Date 10.10.2025

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rabbit
Exposure time	: 4 h
Assessment	: Irritating to skin.
Method	: OECD Test Guideline 404
Result	: Irritating to skin.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE):

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Irritating to skin.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Method	: OECD Test Guideline 404
Result	: Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rabbit
Assessment	: Irritating to eyes.
Method	: OECD Test Guideline 405
Result	: Irritating to eyes.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE):

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: Eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 13.12.2023
1.6	18.09.2024	400001021217	Date of first issue: 20.07.2018

Print Date 10.10.2025

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: The product is a skin sensitiser, sub-category 1B.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE):

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: The product is a skin sensitiser, sub-category 1A.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Exposure routes	: Skin
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells Metabolic activation: without metabolic activation Result: positive
	Test Type: reverse mutation assay Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay) Result: negative
Genotoxicity in vivo	: Test Type: in vivo assay Species: Mouse (male) Cell type: Germ Application Route: Oral Dose: 3333, 10000 mg/kg Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

Test Type: gene mutation test
Species: Rat (male)
Cell type: Somatic
Application Route: Oral
Dose: 50,250,500,1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: negative

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFGE):

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Genotoxicity in vivo : Cell type: Somatic
Application Route: Oral
Exposure time: 48 h
Dose: 2000 mg/kg
Method: OECD Test Guideline 474
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 2000 mg/kg
Method: OECD Test Guideline 486
Result: negative

bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: Positive results were obtained in some in vitro tests.

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rat, male
Application Route	: Oral
Exposure time	: 24 month(s)
Dose	: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	: 7 days/week
NOAEL	: 15 mg/kg bw/day
Method	: OECD Test Guideline 453
Result	: negative
Target Organs	: Digestive organs

Species	: Mouse, male
Application Route	: Dermal
Exposure time	: 24 month(s)
Dose	: 0, 0.1, 10, 100 mg/kg bw/day
Frequency of Treatment	: 3 days/week
NOEL	: 0,1 mg/kg body weight
Method	: OECD Test Guideline 453
Result	: negative
Target Organs	: Digestive organs

Species	: Rat, female
Application Route	: Dermal
Exposure time	: 24 month(s)
Dose	: 0.1, 100, 1000 mg/kg bw/day
Frequency of Treatment	: 5 days/week
NOEL	: 100 mg/kg body weight
Method	: OECD Test Guideline 453
Result	: negative

Species	: Rat, female
Application Route	: Oral
Exposure time	: 24 month(s)
Dose	: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	: 7 days/week
NOAEL	: 100 mg/kg bw/day
Method	: OECD Test Guideline 453
Result	: negative
Target Organs	: Digestive organs

Species	: Rat, females
Application Route	: Oral
Exposure time	: 24 month(s)
Dose	: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	: 7 days/week
NOEL	: 2 mg/kg bw/day
Method	: OECD Test Guideline 453
Result	: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

Target Organs : Digestive organs

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species	: Rat, male and female
Application Route	: Oral
Exposure time	: 24 month(s)
Dose	: 15 mg/kg
Frequency of Treatment	: 7 daily
Method	: OECD Test Guideline 453
Result	: negative

Reproductive toxicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility	: Test Type: Two-generation study Species: Rat, male and female Application Route: Oral Dose: 0, 50, 180, 540 or 750 milligram per kilogram Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily General Toxicity Parent: NOEL: 540 mg/kg body weight General Toxicity F1: NOEL: 750 mg/kg body weight Symptoms: No adverse effects Method: OECD Test Guideline 416 Result: No effects on fertility and early embryonic development were detected.
Effects on fetal development	: Species: Rabbit, female Application Route: Dermal Dose: 0, 30, 100 or 300 milligram per kilogram Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight Method: Other guidelines Result: No teratogenic effects Test Type: Pre-natal Species: Rabbit, female Application Route: Oral Dose: 0, 20, 60 or 180 milligram per kilogram Duration of Single Treatment: 13 d Frequency of Treatment: 1 daily General Toxicity Maternal: NOAEL: 60 mg/kg body weight Developmental Toxicity: NOAEL: 180 mg/kg body weight Method: OECD Test Guideline 414 Result: No teratogenic effects Test Type: Pre-natal Species: Rat, female Application Route: Oral

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Developmental Toxicity: NOAEL: > 540 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE):

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 180, 540 or 750 mg/kg/
Duration of Single Treatment: 238 d
General Toxicity Parent: NOEL: 750
General Toxicity F1: NOEL: 750 mg/kg body weight
General Toxicity F2: NOAEL: 750 mg/kg body weight
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
General Toxicity Parent: NOEL: 750 mg/kg body weight
General Toxicity F1: NOEL: 750 mg/kg body weight
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Effects on fetal development : Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rat, male and female
NOAEL	: 50 mg/kg
Application Route	: oral (gavage)
Exposure time	: 14 Weeks
Number of exposures	: 7 d
Dose	: 0, 50, 250, 1000 mg/kg/day
Method	: OECD Test Guideline 408

Species	: Rat, male and female
NOAEL	: >= 10 mg/kg
Application Route	: Skin contact
Exposure time	: 13 Weeks
Number of exposures	: 5 d
Dose	: 0, 10, 100, 1000 mg/kg/day
Method	: OECD Test Guideline 411

Species	: Mouse, male
NOAEL	: 100 mg/kg
Application Route	: Skin contact
Exposure time	: 13 Weeks
Number of exposures	: 3 d
Dose	: 0, 1, 10, 100 mg/kg/day
Method	: OECD Test Guideline 411

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE):

Species	: Rat, male and female
NOAEL	: 250 mg/kg
Application Route	: Ingestion
Exposure time	: 13 Weeks
Number of exposures	: 7 d
Method	: Subchronic toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species	: Rat, male and female
NOAEL	: 50 mg/kg
Application Route	: Ingestion
Exposure time	: 14 Weeks
Number of exposures	: 7 d
Method	: Subchronic toxicity

Species	: Rat, male and female
NOEL	: 10 mg/kg
Application Route	: Skin contact

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

Exposure time : 13 Weeks
Number of exposures : 5 d
Method : Subchronic toxicity

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 : 11 mg/l
plants
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

NOEC : 4,2 mg/l
Exposure time: 72 h
Test Type: static test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 13.12.2023
1.6	18.09.2024	400001021217	Date of first issue: 20.07.2018

Print Date 10.10.2025

Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other : NOEC: 0,3 mg/l
aquatic invertebrates
(Chronic toxicity) Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFEDGE):

Toxicity to fish : LC50 (Fish): 2,54 mg/l
Exposure time: 96 h
Test substance: Fresh water
Method: Calculation method

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2,55 mg/l
aquatic invertebrates Exposure time: 48 h
Method: Calculation method

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): > 1,8 mg/l
plants Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: no

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
GLP: no

Toxicity to daphnia and other : NOEC: 0,3 mg/l
aquatic invertebrates
(Chronic toxicity) Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 211
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

bisphenol A - epoxy resins, number average MW >700 - <1100:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EgC50 (Selenastrum capricornutum (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability	:	Test Type: aerobic Inoculum: activated sludge, non-adapted Concentration: 20 mg/l Result: Not readily biodegradable. Biodegradation: 5 % Exposure time: 28 d Method: OECD Test Guideline 301F
Stability in water	:	Degradation half life (DT50): 4,83 d (25 °C) pH: 4 Method: OECD Test Guideline 111 Remarks: Fresh water Degradation half life (DT50): 7,1 d (25 °C) pH: 9 Method: OECD Test Guideline 111 Remarks: Fresh water Degradation half life (DT50): 3,58 d (25 °C) pH: 7 Method: OECD Test Guideline 111 Remarks: Fresh water

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE):

Biodegradability	:	Test Type: aerobic Inoculum: activated sludge Concentration: 3 mg/l Result: Not biodegradable Biodegradation: ca. 0 %
------------------	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.E.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Biodegradability	: Test Type: aerobic Inoculum: Sewage (STP effluent) Concentration: 20 mg/l Result: Not biodegradable Biodegradation: 5 % Exposure time: 28 d Method: OECD Test Guideline 301F
Stability in water	: Degradation half life (DT50): 4,83 d (25 °C) pH: 4 Method: OECD Test Guideline 111 Remarks: Fresh water Degradation half life (DT50): 7,1 d (25 °C) pH: 9 Method: OECD Test Guideline 111 Remarks: Fresh water Degradation half life (DT50): 3,58 d (25 °C) pH: 7 Method: OECD Test Guideline 111 Remarks: Fresh water

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation	: Bioconcentration factor (BCF): 31 Remarks: Does not bioaccumulate.
Partition coefficient: n-octanol/water	: log Pow: 3,242 (25 °C) pH: 7,1 Method: OECD Test Guideline 117

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFGE):

Bioaccumulation	: Species: Fish Bioconcentration factor (BCF): 150 Remarks: Does not bioaccumulate.
Partition coefficient: n-octanol/water	: log Pow: 2,7 - 3,6 Method: OECD Test Guideline 117 GLP: yes

bisphenol A - epoxy resins, number average MW >700 - <1100:

Bioaccumulation	: Species: Fish Bioconcentration factor (BCF): 31 Remarks: Does not bioaccumulate.
-----------------	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among : Koc: 445
environmental compartments

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDE):

Distribution among : Koc: 4460
environmental compartments Method: OECD Test Guideline 121

bisphenol A - epoxy resins, number average MW >700 - <1100:

Distribution among : Koc: 445
environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Dispose of contents and container in accordance with all local, regional, national and international regulations. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 3082
ADR	:	UN 3082
RID	:	UN 3082
IMDG	:	UN 3082
IATA	:	UN 3082

14.2 UN proper shipping name

ADN	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)
RID	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)
IATA	:	Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	:	9
ADR	:	9
RID	:	9
IMDG	:	9
IATA	:	9

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: M6
Hazard Identification Number	: 90

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

Labels : 9

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 13.12.2023
1.6	18.09.2024	400001021217	Date of first issue: 20.07.2018

Print Date 10.10.2025

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product does not contain substances of very high concern.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AIIC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.6	18.09.2024	400001021217	13.12.2023
			Date of first issue: 20.07.2018

Print Date 10.10.2025

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AII (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical Safety Assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
DE DFG MAK	: Germany. MAK BAT Annex IIa
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
DE DFG MAK / MAK	: MAK value
DE TRGS 900 / AGW	: Time Weighted Average

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 13.12.2023
1.6	18.09.2024	400001021217	Date of first issue: 20.07.2018

Print Date 10.10.2025

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.