

SAFETY DATA SHEET

RESION EP Floor Cast

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

RESION EP Floor Cast

Product no.

FS202

Unique formula identifier (UFI)

VM60-R0H6-D00T-MFMM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Binder

Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 12	Manufacture of plastics products, including compounding and conversion
SU 19	Building and construction work
Product category	Description
PC 32	Polymer Preparations and Compounds
PC 9a	Coatings and Paints, Fillers, Putties, Thinners
Process category	Description
PROC 19	Hand-mixing with intimate contact and only PPE available
Article category	Description
AC 13	Plastic articles
Environmental release category	Description
ERC 5	Industrial use resulting in inclusion into or onto a matrix
ERC 8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Polyestershoppen BV
Oostbaan 680
2841 ML Moordrecht
Netherlands
+31 85 0220090

Contact person

-

E-mail

info@polyestershoppen.nl

Revision

16/08/2024

SDS Version

2.0

Date of previous version

06/07/2023 (1.0)

1.4. ▼ Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Eye Irrit. 2; H319, Causes serious eye irritation.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

Causes skin irritation. (H315)

May cause an allergic skin reaction. (H317)

Causes serious eye irritation. (H319)

Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention

Avoid breathing mist/vapour. (P261)

Wash hands thoroughly after handling. (P264)

Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF ON SKIN: Wash with plenty of water and soap. (P302+P352)

If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)

Storage

-

▼ Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

reaction product: bisphenol-A(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Additional labelling

EUH205, Contains epoxy constituents. May produce an allergic reaction.

UFI: VM60-R0H6-D00T-MFMM

2.3. Other hazards

▼ Additional warnings

Contains epoxy constituents. May produce an allergic reaction.

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)	CAS No.: 25068-38-6 EC No.: 500-033-5 UK-REACH: Index No.: 603-074-00-8	15-25%	EUH205 Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Aquatic Chronic 2, H411	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	CAS No.: 9003-36-5 EC No.: 500-006-8 UK-REACH: Index No.:	3-5%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS No.: 68609-97-2 EC No.: 271-846-8 UK-REACH: Index No.: 603-103-00-4	3-5%	Skin Irrit. 2, H315 Skin Sens. 1, H317	[19]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

▼ Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Sulphur oxides

Carbon oxides (CO / CO₂)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact

The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼ Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage conditions

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Barium sulfate

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

Quartz (SiO₂)

Long term exposure limit (8 hours) (mg/m³): 0,1 (respirable fraction)

Annotations:

Carc = Capable of causing cancer and/or heritable genetic damage.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

Barium sulfate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	10 mg/m ³
Long term – Systemic effects - General population	Inhalation	10 mg/m ³
Long term – Systemic effects - Workers	Inhalation	10 mg/m ³
Long term – Systemic effects - General population	Oral	13000 mg/kg bw/day

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62.5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	104.15 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	8.7 mg/m ³
Long term – Systemic effects - Workers	Inhalation	29.39 mg/m ³
Long term – Systemic effects - General population	Oral	6.25 mg/kg bw/day

reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	8.33 mg/kg
Short term – Local effects - Workers	Dermal	8.33 mg/kg
Long term – Systemic effects - Workers	Inhalation	0.012 mg/L
Short term – Local effects - Workers	Inhalation	0.012 mg/L

PNEC

Barium sulfate		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		115 µg/L
Freshwater sediment		600.4 mg/kg
Sewage treatment plant		62.2 mg/L
Soil		207.7 mg/kg

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0.003 mg/L
Freshwater sediment		0.294 mg/kg
Intermittent release	Single	0.025 mg/L
Marine water	Single	0 mg/L
Marine water sediment	Single	0.029 mg/kg
Sewage treatment plant	Single	10 mg/L
Soil	Single	0.237 mg/kg

reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0.006 mg/L
Freshwater sediment	Single	0.0627 mg/L
Marine water	Single	0.0006 mg/L
Marine water sediment	Single	0.00627 mg/L
Sewage treatment plant	Single	10 mg/L

8.2. ▼ Exposure controls

Apply general control to prevent unnecessary exposure

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

▼ Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

▼ Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
No special when used as intended.			

Skin protection

Recommended	Type/Category	Standards
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.	-	-



Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388



Eye protection

Type	Standards
Safety glasses with side shields.	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Beige, sand

Odour / Odour threshold

Characteristic

▼ pH

No relevant or available data due to the nature of the product.

▼ Density (g/cm³)

No relevant or available data due to the nature of the product.

▼ Kinematic viscosity

No relevant or available data due to the nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

▼ Melting point/Freezing point (°C)

No relevant or available data due to the nature of the product.

Softening point/range (°C)

Does not apply to liquids.

▼ Boiling point (°C)

No relevant or available data due to the nature of the product.

▼ Vapour pressure

No relevant or available data due to the nature of the product.

▼ Relative vapour density

No relevant or available data due to the nature of the product.

▼ Decomposition temperature (°C)

No relevant or available data due to the nature of the product.

Data on fire and explosion hazards

▼ Flash point (°C)

No relevant or available data due to the nature of the product.

▼ Flammability (°C)

No relevant or available data due to the nature of the product.

▼ Auto-ignition temperature (°C)

No relevant or available data due to the nature of the product.

▼ Lower and upper explosion limit (% v/v)

No relevant or available data due to the nature of the product.

Solubility

Solubility in water

Slightly soluble

▼ n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.

▼ Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

▼ Oxidizing properties

No relevant or available data due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight $\leq$ 700)
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	15000 mg/kg

Product/substance	reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	23000 mg/kg

▼ Skin corrosion/irritation

Product/substance	reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)
Result:	Adverse effect observed (Irritating)

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

Quartz (SiO₂) has been classified by IARC as a group 1 carcinogen.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance	Barium sulfate
Test method:	OECD 203
Species:	Fish, Danio rerio
Test:	LC50
Result:	>3,5 mg/L

Product/substance	Barium sulfate
Species:	Crustacean, Daphnia magna
Test:	EC50
Result:	14,5 mg/L

Product/substance	Barium sulfate
Test method:	OECD 201

Species: Algae, *Pseudokirchneriella subcapitata*
Result: >100 mg/L

Product/substance: Barium sulfate
Test method: OECD 210
Species: Fish, *Danio rerio*
Test: NOEC
Result: >100 mg/L

Product/substance: Barium sulfate
Test method: OECD 201
Species: Algae, *Pseudokirchneriella subcapitata*
Test: NOEC
Result: >100 mg/L

Product/substance: reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)
Species: *Daphnia*
Compartment: Freshwater
Duration: 21 days
Test: NOEC
Result: 0.3 mg/L

Product/substance: reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)
Species: *Daphnia*
Compartment: Freshwater
Duration: 48 hours
Test: EC50
Result: 1.8 mg/L

Product/substance: reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)
Species: Fish
Duration: 96 hours
Test: LC50
Result: 2 mg/L

Harmful to aquatic life with long lasting effects.

12.2. ▼ Persistence and degradability

Product/substance: reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)
Conclusion: Not biodegradable

12.3. ▼ Bioaccumulative potential

Product/substance: Barium sulfate
BCF: <500
Conclusion: No potential for bioaccumulation

12.4. Mobility in soil

No data available.

12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations



13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 4 - Irritant (skin irritation and eye damage)

HP 13 - Sensitising

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

▼ EWC code

08

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700))	Transport hazard class: 9 Label: 9 Classification code: M6 	III	No	Limited quantities: 5 L Tunnel restriction code: (-) See below for additional information.
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700))	Transport hazard class: 9 Label: 9 Classification code: M6 	III	No	Limited quantities: 5 L EmS: F-A S-F See below for additional information.
IATA	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700))	Transport hazard class: 9 Label: 9 Classification code: M6 	III	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR/IMDG/IATA provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (ADR, IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

Use of this product requires dedicated training in work with polyurethane and epoxy products.

SEVESO - Categories / dangerous substances

Not applicable.

Additional information

Not applicable.

Sources

The Management of Health and Safety at Work Regulations 1999.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)

LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU 12 = Manufacture of plastics products, including compounding and conversion

SU 19 = Building and construction work

PROC 19 = Hand-mixing with intimate contact and only PPE available

PC 32 = Polymer Preparations and Compounds

PC 9a = Coatings and Paints, Fillers, Putties, Thinners

AC 13 = Plastic articles

ERC 5 = Industrial use resulting in inclusion into or onto a matrix

ERC 8c = Wide dispersive indoor use resulting in inclusion into or onto a matrix

▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The safety data sheet is validated by

H.A.B.

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en