

SAFETY DATA SHEET

RESION Polyester Primer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

RESION Polyester Primer

Product no.

PR95

Unique formula identifier (UFI)

46D0-N0D0-900Y-MNGT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Paint

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Polyestershoppen BV

Oostbaan 680
2841 ML Moordrecht
Netherlands
+31 85 0220090

Contact person

-

E-mail

info@polyestershoppen.nl

Revision

13/12/2023

SDS Version

2.0

Date of previous version

16/11/2022 (1.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).
See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

Skin Irrit. 2; H315, Causes skin irritation.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Eye Irrit. 2; H319, Causes serious eye irritation.

Acute Tox. 4; H332, Harmful if inhaled.

Resp. Sens. 1; H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT SE 3; H335, May cause respiratory irritation.

Carc. 2; H351, Suspected of causing cancer.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Flammable liquid and vapour. (H226)
Causes skin irritation. (H315)
May cause an allergic skin reaction. (H317)
Causes serious eye irritation. (H319)
Harmful if inhaled. (H332)
May cause allergy or asthma symptoms or breathing difficulties if inhaled. (H334)
May cause respiratory irritation. (H335)
Suspected of causing cancer. (H351)
May cause damage to organs through prolonged or repeated exposure. (H373)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

Prevention

Obtain special instructions before use. (P201)
Do not breathe vapour/mist. (P260)

Response

IF exposed or concerned: Get medical advice/attention. (P308+P313)
Get medical advice/attention if you feel unwell. (P314)

Storage

Store locked up. (P405)

▼ Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

m-xylene;xylene;o-xylene;p-xylene
Isocyanic acid, polymethylenepolyphenylene ester
4-isocyanatosulphonyltoluene;tosyl isocyanate

▼ Additional labelling

EUH204, Contains isocyanates. May produce an allergic reaction.
As from 24 August 2023 adequate training is required before industrial or professional use.
UFI: 46D0-N0D0-900Y-MNGT

2.3. Other hazards

▼ Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. ▼ Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

| Product/substance | Identifiers | % w/w | Classification | Note |
|-----------------------------|--------------------|--------|--------------------|------|
| m-xylene;xylene;o-xylene;p- | CAS No.: 1330-20-7 | 40-60% | Flam. Liq. 3, H226 | [1] |

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

| | | | |
|--|---|--------|---|
| xylene | EC No.: 215-535-7 UK-REACH: Index No.: 601-022-00-9 | | Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332 |
| Isocyanic acid, polymethylenepolyphenylene ester | CAS No.: 9016-87-9 EC No.: 618-498-9 UK-REACH: Index No.: | 40-60% | EUH204 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373 |
| Propane-1,2-diol, propoxylated | CAS No.: 25322-69-4 EC No.: 500-039-8 UK-REACH: Index No.: | 5-10% | Acute Tox. 4, H302 |
| 4- isocyanatosulphonyltoluene;t osyl isocyanate | CAS No.: 4083-64-1 EC No.: 223-810-8 UK-REACH: Index No.: 615-012-00-7 | <1% | EUH014 Skin Irrit. 2, H315 (SCL: 5.00 %) Eye Irrit. 2, H319 Resp. Sens. 1, H334 STOT SE 3, H335 (SCL: 5.00 %) |

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

▼ Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.

▼ Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

▼ Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. ▼ Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. ▼ Special hazards arising from the substance or mixture

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact

The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. ▼ Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼ Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

- Use non-sparking tools.
- Take action to prevent static discharges.
- Avoid direct contact with the product.
- Avoid contact during pregnancy and while nursing.
- Smoking, drinking and consumption of food is not allowed in the work area.
- See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

- Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
- Take action to prevent static discharges.
- Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Keep only in original packaging.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. ▼ Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

- m-xylene;xylene;o-xylene;p-xylene
- Long term exposure limit (8 hours) (ppm): 50
- Long term exposure limit (8 hours) (mg/m³): 220
- Short term exposure limit (15 minutes) (ppm): 100
- Short term exposure limit (15 minutes) (mg/m³): 441
- Annotations:
- BMVG = Biological Monitoring Guidance Value exists
- Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

4-isocyanatosulphonyltoluene;tosyl isocyanate

| Duration: | Route of exposure: | DNEL: |
|---|--------------------|------------------------|
| Long term – Systemic effects - General population | Dermal | 460 µg/kgbw/day |
| Long term – Systemic effects - Workers | Dermal | 920 µg/kgbw/day |
| Long term – Systemic effects - General population | Inhalation | 800 µg/m ³ |
| Long term – Systemic effects - Workers | Inhalation | 3.24 mg/m ³ |
| Long term – Systemic effects - General population | Oral | 460 µg/kgbw/day |

m-xylene;xylene;o-xylene;p-xylene

| Duration: | Route of exposure: | DNEL: |
|---|--------------------|------------------------|
| Long term – Systemic effects - General population | Dermal | 125 mg/kg bw/day |
| Long term – Systemic effects - Workers | Dermal | 212 mg/kg bw/day |
| Long term – Local effects - General population | Inhalation | 65.3 mg/m ³ |
| Long term – Local effects - Workers | Inhalation | 221 mg/m ³ |
| Long term – Systemic effects - General population | Inhalation | 65.3 mg/m ³ |
| Long term – Systemic effects - Workers | Inhalation | 221 mg/m ³ |
| Short term – Local effects - General population | Inhalation | 260 mg/m ³ |

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

| | | |
|--|------------|-----------------------|
| Short term – Local effects - Workers | Inhalation | 442 mg/m ³ |
| Short term – Systemic effects - General population | Inhalation | 260 mg/m ³ |
| Short term – Systemic effects - Workers | Inhalation | 442 mg/m ³ |
| Long term – Systemic effects - General population | Oral | 12.5 mg/kg bw/day |

Propane-1,2-diol, propoxylated

| Duration: | Route of exposure: | DNEL: |
|---|--------------------|----------------------|
| Long term – Systemic effects - General population | Dermal | 8.3 mg/kg bw/day |
| Long term – Systemic effects - Workers | Dermal | 13.9 mg/kg bw/day |
| Long term – Local effects - General population | Inhalation | 10 mg/m ³ |
| Long term – Local effects - Workers | Inhalation | 10 mg/m ³ |
| Long term – Systemic effects - General population | Inhalation | 29 mg/m ³ |
| Long term – Systemic effects - Workers | Inhalation | 98 mg/m ³ |
| Long term – Systemic effects - General population | Oral | 8.3 mg/kg bw/day |

▼ PNEC

4-isocyanatosulphonyltoluene;tosyl isocyanate

| Route of exposure: | Duration of Exposure: | PNEC: |
|-----------------------------------|-----------------------|------------|
| Freshwater | | 30 µg/L |
| Freshwater sediment | | 172 µg/kg |
| Intermittent release (freshwater) | | 300 µg/L |
| Marine water | | 3 µg/L |
| Marine water sediment | | 17.2 µg/kg |
| Sewage treatment plant | | 400 µg/L |
| Soil | | 16.8 µg/kg |

m-xylene;xylene;o-xylene;p-xylene

| Route of exposure: | Duration of Exposure: | PNEC: |
|-----------------------------------|-----------------------|-------------|
| Freshwater | | 327 µg/L |
| Freshwater sediment | | 12.46 mg/kg |
| Intermittent release (freshwater) | | 327 µg/L |
| Marine water | | 327 µg/L |
| Marine water sediment | | 12.46 mg/kg |
| Sewage treatment plant | | 6.58 mg/L |
| Soil | | 2.31 mg/kg |

Propane-1,2-diol, propoxylated

| Route of exposure: | Duration of Exposure: | PNEC: |
|-----------------------------------|-----------------------|-----------------|
| Freshwater | | 100-200 µg/L |
| Freshwater sediment | | 419-765 µg/kg |
| Intermittent release (freshwater) | | 1-1.06 mg/L |
| Marine water | | 10-20 µg/L |
| Marine water sediment | | 41.9-76.5 µg/kg |
| Sewage treatment plant | | 100 mg/L |
| Soil | | 30.6-109 µg/kg |

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼ Appropriate technical measures

Do not recirculate outlet air that contain the substances.

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (e.g. type A1 according to standard EN 14387) is used.

Use only UKCA marked protective equipment.

Respiratory Equipment

| Work situation | Type | Class | Colour | Standards |
|-----------------------------------|------|---------------------------|--------|-----------|
| In case of inadequate ventilation | A | Class 2 (medium capacity) | Brown | EN14387 |



Skin protection

| Recommended | Type/Category | Standards |
|---|---------------|-----------|
| Dedicated work clothing should be worn. | - | - |



Hand protection

| Material | Glove thickness (mm) | Breakthrough time (min.) | Standards |
|----------|----------------------|--------------------------|-------------------------|
| Nitrile | 0,2 | > 240 | EN374-2, EN374-3, EN388 |



Eye protection

| Type | Standards |
|-----------------------------------|-----------|
| Safety glasses with side shields. | EN166 |



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Brown

Odour / Odour threshold

Characteristic

pH

Testing not relevant or not possible due to the nature of the product.

Density (g/cm³)

0.98

Kinematic viscosity

100 mPa.s

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

137

Vapour pressure

6.7 hPa

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to the nature of the product.

▼ Flammability (°C)

The material is ignitable.

▼ Auto-ignition temperature (°C)

500

Lower and upper explosion limit (% v/v)

1.1 - 7

Solubility

Solubility in water

Testing not relevant or not possible due to the nature of the product.

n-octanol/water coefficient (LogKow)

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

VOC (g/L)

500

Other physical and chemical parameters

No data available.

▼ Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

| | |
|--------------------|-----------------------------------|
| Product/substance | m-xylene;xylene;o-xylene;p-xylene |
| Species: | Rat |
| Route of exposure: | Oral |
| Test: | LD50 |
| Result: | 4300 mg/kg |

| | |
|--------------------|-----------------------------------|
| Product/substance | m-xylene;xylene;o-xylene;p-xylene |
| Species: | Rabbit |
| Route of exposure: | Dermal |
| Test: | LD50 |
| Result: | 2000 mg/kg |

| | |
|--------------------|--|
| Product/substance | Isocyanic acid, polymethylenepolyphenylene ester |
| Species: | Rat |
| Route of exposure: | Oral |
| Test: | LD50 |
| Result: | 10000 mg/kg |

| | |
|--------------------|--|
| Product/substance | Isocyanic acid, polymethylenepolyphenylene ester |
| Species: | Rabbit |
| Route of exposure: | Dermal |
| Test: | LD50 |
| Result: | 9400 mg/kg |

| | |
|--------------------|--|
| Product/substance | Isocyanic acid, polymethylenepolyphenylene ester |
| Species: | Rat |
| Route of exposure: | Inhalation |
| Test: | LC50 (4 hours) |
| Result: | 490 mg/L |

Harmful if inhaled.

▼ Skin corrosion/irritation

| | |
|-------------------|--|
| Product/substance | Isocyanic acid, polymethylenepolyphenylene ester |
| Result: | Adverse effect observed (Irritating) |

Causes skin irritation.

▼ Serious eye damage/irritation

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance: Isocyanic acid, polymethylenepolyphenylene ester
 Result: Adverse effect observed (Highly irritating)

Causes serious eye irritation.

▼ Respiratory sensitisation

Product/substance: Isocyanic acid, polymethylenepolyphenylene ester
 Result: Adverse effect observed (sensitising)

▼ Skin sensitisation

Product/substance: Isocyanic acid, polymethylenepolyphenylene ester
 Result: Adverse effect observed (sensitising)

▼ Germ cell mutagenicity

Product/substance: Isocyanic acid, polymethylenepolyphenylene ester
 Conclusion: No adverse effect observed

Carcinogenicity

Suspected of causing cancer.

▼ Reproductive toxicity

Product/substance: Isocyanic acid, polymethylenepolyphenylene ester
 Conclusion: No adverse effect observed

▼ STOT-single exposure

Product/substance: Isocyanic acid, polymethylenepolyphenylene ester
 Target organ: Lung
 Conclusion: Adverse effect observed

May cause respiratory irritation.

▼ STOT-repeated exposure

Product/substance: Isocyanic acid, polymethylenepolyphenylene ester
 Conclusion: Adverse effect observed

May cause damage to organs through prolonged or repeated exposure.

▼ Aspiration hazard

Product/substance: Isocyanic acid, polymethylenepolyphenylene ester
 Conclusion: Aspiration hazard not applicable

11.2. Information on other hazards

Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

m-xylene;xylene;o-xylene;p-xylene has been classified by IARC as a group 3 carcinogen.

Isocyanic acid, polymethylenepolyphenylene ester has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. ▼ Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 6 - Acute toxicity

HP 7 - Carcinogenic

HP 13 - Sensitising

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.



▼ EWC code

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

| | 14.1 UN / ID | 14.2 UN proper shipping name | 14.3 Hazard class(es) | 14.4 PG* | 14.5 Env** | Other information: |
|------|-----------------|--|---|-------------|---------------|--|
| ADR | UN1993 | FLAMMABLE LIQUID, N.O.S. (m-xylene;xylene;o-xylene;p-xylene) | Transport hazard class: 3 Label: 3 Classification code: F1  | III | No | Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information. |
| IMDG | UN1993 | FLAMMABLE LIQUID, N.O.S. (m-xylene;xylene;o-xylene;p-xylene) | Transport hazard class: 3 Label: 3 Classification code: F1  | III | No | Limited quantities: 5 L EmS: F-E S-E See below for additional information. |
| IATA | UN1993 | FLAMMABLE LIQUID, N.O.S. (m-xylene;xylene;o-xylene;p-xylene) | Transport hazard class: 3 Label: 3 Classification code: F1 | III | No | See below for additional information. |

| 14.1 UN / ID | 14.2 UN proper shipping name | 14.3 Hazard class(es) | 14.4 PG* | 14.5 Env** | Other information: |
|-----------------|---------------------------------|---|-------------|---------------|-----------------------|
| | |  | | | |

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

Use of this product requires dedicated training in work with polyurethane and epoxy products.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

▼ REACH, Annex XVII

RESION Polyester Primer is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 3).

Isocyanic acid, polymethylenepolyphenylene ester is subject to restrictions, UK-REACH annex XVII (entry 74).

RESION Polyester Primer is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 40).

m-xylene;xylene;o-xylene;p-xylene is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 40).

Additional information

Tactile warning.

Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

EUH014, Reacts violently with water.
EUH204, Contains isocyanates. May produce an allergic reaction.
H226, Flammable liquid and vapour.
H302, Harmful if swallowed.
H312, Harmful in contact with skin.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335, May cause respiratory irritation.
H351, Suspected of causing cancer.
H373, May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

▼ The safety data sheet is validated by

H.A.B.

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue

triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en