

SAFETY DATA SHEET

RESION Marine Sealant

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

RESION Marine Sealant

Product no.

PU60

Unique formula identifier (UFI)

TYD0-60KK-200E-KQRD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Filler

Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 19	Building and construction work
Product category	Description
PC 1	Adhesives, Sealants
Process category	Description
PROC 19	Hand-mixing with intimate contact and only PPE available

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Polyestershoppen BV
Oostbaan 680
2841 ML Moordrecht
Netherlands
+31 85 0220090

Contact person

-

E-mail

info@polyestershoppen.nl

Revision

29/06/2023

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).
See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.
Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour. (H225)
May be fatal if swallowed and enters airways. (H304)
Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Avoid release to the environment. (P273)

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)
Do NOT induce vomiting. (P331)

Storage

Store locked up. (P405)

Disposal

Dispose of contents/container in accordance with in accordance with local regulation (P501)

Hazardous substances

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F).]

Additional labelling

UFI: TYD0-60KK-200E-KQRD

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance	Identifiers	% w/w	Classification	Note
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F).]	CAS No.: 64742-49-0 EC No.: 265-151-9 UK-REACH: Index No.: 649-328-00-1	15-25%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[19]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Keep only in original packaging.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No substances are listed in the national list of substances with an occupational exposure limit.

DNEL

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F).]

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	149 mg/kg bw/day
Long term – Systemic effects - General population	Dermal	1377 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	300 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	13964 mg/kg bw/day
Long term – Local effects - General population	Inhalation	178.57 mg/m ³
Long term – Local effects - Workers	Inhalation	837.5 mg/m ³
Long term – Systemic effects - General population	Inhalation	410 µg/m ³
Long term – Systemic effects - General population	Inhalation	447 mg/m ³
Long term – Systemic effects - General population	Inhalation	1131 mg/m ³
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m ³
Long term – Systemic effects - Workers	Inhalation	2085 mg/m ³
Long term – Systemic effects - Workers	Inhalation	5306 mg/m ³
Short term – Local effects - General population	Inhalation	640 mg/m ³
Short term – Local effects - Workers	Inhalation	1066.67 mg/m ³
Short term – Systemic effects - General population	Inhalation	1152 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m ³
Long term – Systemic effects - General population	Oral	149 mg/kg bw/day
Long term – Systemic effects - General population	Oral	1301 mg/kg bw/day

PNEC

No data available.

8.2. Exposure controls

Control is unnecessary if the product is used as intended.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

No specific requirements

Skin protection

Recommended	Type/Category	Standards
No special when used as intended.	-	-

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,2	> 240	EN374-2, EN374-3, EN388



Eye protection

Type	Standards
Safety glasses with side shields.	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Paste

Colour

Various colours

Odour / Odour threshold

Characteristic

pH

Testing not relevant or not possible due to the nature of the product.

Density (g/cm³)

Testing not relevant or not possible due to the nature of the product.

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Dynamic viscosity

>20,5 centistokes (40 °C)

Particle characteristics

Testing not relevant or not possible due to the nature of the product.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Boiling point (°C)

80

Vapour pressure

6000 Pa (20 °C)

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

-10

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

200

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Naphtha (petroleum), hydrotreated light;Low boiling point hydrogen treated naphtha;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F).]
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5100 mg/kg

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance	Naphtha (petroleum), hydrotreated light;Low boiling point hydrogen treated naphtha;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F).]
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	3160 mg/kg

Product/substance	Naphtha (petroleum), hydrotreated light;Low boiling point hydrogen treated naphtha;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F).]
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	12 mg/L

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

Not applicable.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	Naphtha (petroleum), hydrotreated light;Low boiling point hydrogen treated naphtha;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F).]
Species:	Crustacean
Duration:	96 hours
Test:	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Result: 4,3 mg/L

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

Product/substance Naphtha (petroleum), hydrotreated light;Low boiling point hydrogen treated naphtha;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F).]

Test method:

Potential bioaccumulation: Yes

LogPow: 3,7

BCF: 380

Other information:

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

This product contains substances with the potential of bioaccumulation resulting in the risk of accumulation in the food chain. Bioaccumulative substances are concentrated in adipose tissue and are not easily secreted.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.


EWC code

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances



Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1	II	No	Limited quantities: 5 L EmS: F-E S-D

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
					See below for additional information.
IATA	UN1133 ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

Additional information

Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

H304, May be fatal if swallowed and enters airways.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)

LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU 19 = Building and construction work

PROC 19 = Hand-mixing with intimate contact and only PPE available

PC 1 = Adhesives, Sealants

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

H.A.B.

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en