

# SAFETY DATA SHEET

# **RESION EP-MONOTint, EP-PastelTint**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

### Trade name

**RESION EP-MONOTint, EP-PastelTint** 

### ▼ Product no. EP901, EP903

Unique formula identifier (UFI) 3A50-5057-T00D-QAVN

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Relevant identified uses of the substance or mixture

# Filler

### Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 12	Manufacture of plastics products, including compounding and conversion
SU 19	Building and construction work
Product category	Description
PC 32	Polymer Preparations and Compounds
Process category	Description
PROC 19	Hand-mixing with intimate contact and only PPE available
PROC 2	Use in closed, continuous PROC ess with occasional controlled exposure
PROC 5	Mixing or blending in batch PROC esses for formulation of preparations and articles (multistage and/or significant contact)
Article category	Description
AC 13	Plastic articles
Environmental release category	Description
ERC 3	Formulation in materials
ERC 5	Industrial use resulting in inclusion into or onto a matrix
ERC 8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
ERC 8f	Wide dispersive outdoor use resulting in inclusion into or onto a matrix

# Uses advised against

None known.

# 1.3. Details of the supplier of the safety data sheet

# Company and address Polyestershoppen BV

Oostbaan 680 2841 ML Moordrecht Netherlands



+31 85 0220090

Contact person

E-mail info@polyestershoppen.nl

Revision 14/12/2023

SDS Version 3.0

Date of previous version 14/12/2023 (3.0)

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

# SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation. Skin Sens. 1; H317, May cause an allergic skin reaction. Eye Irrit. 2; H319, Causes serious eye irritation. Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

### 2.2. Label elements



Signal word Warning

### Hazard statement(s)

Causes skin irritation. (H315) May cause an allergic skin reaction. (H317) Causes serious eye irritation. (H319) Toxic to aquatic life with long lasting effects. (H411)

### Precautionary statement(s)

# General

If medical advice is needed, have product container or label at hand. (P101) Keep out of reach of children. (P102)

### Prevention

Avoid breathing mist/vapour. (P261) Wash hands thoroughly after handling. (P264) Wear eye protection/protective gloves/protective clothing. (P280)

### Response

IF ON SKIN: Wash with plenty of water and soap. (P302+P352)

If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)

# Storage

### Disposal

Dispose of contents/container in accordance with local regulation (P501)

# Hazardous substances

bis-[4-(2,3-epoxipropoxi)phenyl]propane Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol



Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

#### Additional labelling

EUH205, Contains epoxy constituents. May produce an allergic reaction. EUH211, Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. UFI: 3A50-5057-T00D-QAVN

### 2.3. Other hazards

# Additional warnings

Contains epoxy constituents. May produce an allergic reaction.

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substanceIdentifiers% w/wClassificationbis-[4-(2,3- epoxipropoxi)phenyl]propaneCAS No.: 1675-54-3 EC No.: 216-823-5 UK-REACH: Index No.: 603-073-00-225-40%Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Aquatic Chronic 2, H411Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenolCAS No.: 9003-36-5 EC No.: 500-006-8 UK-REACH: Index No.:1-3%Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411Reaction products of hexane- 1,6-diol with 2- (chloromethylovirane (1:2)CAS No.: 933999-84-9 EC No.: 618-939-51-3%Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411					
epoxipropoxi)phenyl]propaneEC No.: 216-823-5 UK-REACH: Index No.: 603-073-00-2Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Aquatic Chronic 2, H411Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenolCAS No.: 9003-36-5 EC No.: 500-006-8 UK-REACH: Index No.:1-3%Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411Reaction products of hexane- 1,6-diol with 2-CAS No.: 933999-84-9 EC No.: 618-939-51-3%Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	oduct/substance	Identifiers	% w/w	Classification	Note
reaction products with 1- chloro-2,3-epoxypropane and phenolEC No.: 500-006-8 UK-REACH: Index No.:Skin Sens. 1, H317 Aquatic Chronic 2, H411Reaction products of hexane- 1,6-diol with 2-CAS No.: 933999-84-9 EC No.: 618-939-51-3% Skin Irrit. 2, H315 Skin Sens. 1, H317	2 ( )	EC No.: 216-823-5 UK-REACH:	25-40%	Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %)	
1,6-diol with 2- EC No.: 618-939-5 Skin Sens. 1, H317	action products with 1- loro-2,3-epoxypropane and	EC No.: 500-006-8 UK-REACH:	1-3%	Skin Sens. 1, H317	
Index No.: Eye Int. 2, HS19 Aquatic Chronic 3, H412		EC No.: 618-939-5 UK-REACH:	1-3%	Skin Sens. 1, H317 Eye Irrit. 2, H319	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

# Other information

# SECTION 4: First aid measures

# 4.1. Description of first aid measures

### **General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

### Eye contact



If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

#### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

### **Burns**

Not applicable.

### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs: Get medical advice/attention.

### Information to medics

Bring this safety data sheet or the label from this product.

# SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

# 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

# SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

# 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and



surrounding environment.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### Recommended storage material

Keep only in original packaging.

Storage temperature

Dry, cool and well ventilated

# Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq$  10 µm] Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 10(inhalable)/4(respirable)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

#### DNEL

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	0.0893 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	0.75 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	0.87 mg/m3
Long term – Systemic effects - Workers	Inhalation	4.93 mg/m3
Short term – Systemic effects - General population	Oral	0.5 mg/kg bw/day

Duratio	Pouto of overcourse	DNEL
Formald	dehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	

Duration.	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62.5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	104.15 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	8.7 mg/m3
Long term – Systemic effects - Workers	Inhalation	29.39 mg/m3
Long term – Systemic effects - General population	Oral	6.25 mg/kg bw/day

# Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	13.6 µg/cm²
Long term – Local effects - Workers	Dermal	22.6 µg/cm²
Long term – Systemic effects - General population	Dermal	3 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	6 mg/kg bw/day
Short term – Local effects - General population	Dermal	13.6 µg/cm²
Short term – Local effects - Workers	Dermal	22.6 µg/cm²
Long term – Local effects - General population	Inhalation	270 µg/m³
Long term – Local effects - Workers	Inhalation	440 µg/m³



Long term – Systemic effects - General population	Inhalation	5.29 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	10.57 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	5.29 mg/m³
Short term – Systemic effects - Workers	Inhalation	10.57 mg/m³
Long term – Systemic effects - General population	Oral	1.5 mg/kg bw/day
Short term – Systemic effects - General population	Oral	1.5 mg/kg bw/day

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]Duration:Route of exposure:DNEL:Long term - Local effects - General populationInhalation28 μg/m³

Inhalation

# PNEC

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Long term – Local effects - Workers

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0.006 mg/L
Freshwater sediment	Single	0.341 mg/kg
Marine water	Single	0.001 mg/L
Marine water sediment	Single	0.034 mg/kg
Sewage treatment plant	Single	10 mg/L
Soil	Single	0.065 mg/kg

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Route of exposure:	<b>Duration of Exposure:</b>	PNEC:
Freshwater	Single	0.003 mg/L
Freshwater sediment		0.294 mg/kg
Intermittent release	Single	0.025 mg/L
Marine water	Single	0 mg/L
Marine water sediment	Single	0.029 mg/kg
Sewage treatment plant	Single	10 mg/L
Soil	Single	0.237 mg/kg

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		11.5 μg/L
Freshwater sediment		283 µg/kg
Intermittent release (freshwater)		115 µg/L
Marine water		1.15 μg/L
Marine water sediment		28.3 µg/kg
Sewage treatment plant		1 mg/L
Soil		223 µg/kg

# 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

# General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

#### Exposure scenarios

There are no exposure scenarios implemented for this product.

**Exposure limits** 

170 µg/m<sup>3</sup>



Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

# Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

Take off contaminated clothing and wash it before reuse.

### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

#### Generally

Use only UKCA marked protective equipment.

### Respiratory Equipment

	Туре	Class	Colour		Standards	
	No special when used as intended.					
Ski	n protection					
	Recommended	Type/Category		Standards		
	Dedicated work clothing should be worn.	-		-		R

### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,2	> 240	EN374-2, EN374-3, EN388	

### Eye protection

Туре	Standards
Safety glasses with side shields.	EN166



# SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Paste Colour Various colours Odour / Odour threshold Characteristic pH Testing not relevant or not possible due to the nature of the product.

# Density (g/cm<sup>3</sup>) 1.766 Kinematic viscosity



Testing not relevant or not possible due to the nature of the product.

### Particle characteristics

Testing not relevant or not possible due to the nature of the product.

#### Phase changes

# Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

### Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

### Vapour pressure

Testing not relevant or not possible due to the nature of the product.

### Relative vapour density

Testing not relevant or not possible due to the nature of the product.

## Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

### Data on fire and explosion hazards

Flash point (°C)

>150

# Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

### Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

### Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

# Solubility

### Solubility in water

Testing not relevant or not possible due to the nature of the product.

### n-octanol/water coefficient (LogKow)

Testing not relevant or not possible due to the nature of the product.

### Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

### 9.2. Other information

Other physical and chemical parameters No data available.

# **Oxidizing properties**

Testing not relevant or not possible due to the nature of the product.

### SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid None known.

# 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.



# SECTION 11: Toxicological information

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10
Product/substance	μm]
Test method:	OECD 401
Species:	Rat, male/female
Route of exposure:	Oral
Test:	LD50
Result:	>2000 mg/kgbw
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu$ m]
Test method:	OECD 403
Species:	Rat, male
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	>5.09 mg/L
Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	15000 mg/kg
Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	23000 mg/kg
Product/substance	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	2900 mg/kg
Product/substance	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	>4900 mg/kg
Skin corrosion/irritation	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10
Product/substance	μm]
Test method:	OECD 404
Species:	Rabbit
Duration:	4 hours
Result:	No adverse effect observed (Not irritating)
Causes skin irritation. Serious eye damage/irrita	tion
Causes serious eye irrit	
Respiratory sensitisation	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10
Product/substance	μm]
Test method:	OECD 429
Species:	Mouse, female



Result:	No adverse effect observed (not sensitising)
kin sensitisation	
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤
	μm]
Test method:	OECD 429
Species:	Mouse, female
Result:	No adverse effect observed (not sensitising)
erm cell mutagenicity	
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$
	µm]
Test method:	OECD 473
Species:	Mouse, Chinese Hamster Ovary (CHO)
Conclusion:	No adverse effect observed
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$
	µm]
Test method:	OECD 471
Species:	Bacteria, S. typhimurium
Conclusion:	No adverse effect observed
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$
i i oddeb substance	µm]
Test method:	OECD 474
Species:	Mouse, male/female
Conclusion:	No adverse effect observed
arcinogenicity	
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$
FIGUUCI/Substance	µm]
Test method:	OESO 453
Species:	Rat, male/female
Route of exposure:	Inhalation
Target organ:	Lung
Duration:	24 months
Test:	NOAEC
Result:	5 mg/m <sup>3</sup>
Conclusion:	No adverse effect observed
Draduct/outbatanas	titanium diauida. Fin nauudau fauna aantaining 1.0/ au naug of nautielaa wikk aanadumanais diamatau k
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq \mu m$ ]
Species:	Rat, male/female
Route of exposure:	Oral
Duration:	24 months
Test:	NOAEL
Result:	50000 ppm
Conclusion:	No adverse effect observed
eproductive toxicity	
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$
	µm]
Test method:	OECD 414
Species:	Rat
Duration:	14 days
Test:	NOAEL
Result:	1000 mg/kg bw/day
Conclusion:	No adverse effect observed
Conclusion.	

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.



### Aspiration hazard

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards

# Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

# Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

# Other information

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq$  10 µm] has been classified by IARC as a group 2B carcinogen.

bis-[4-(2,3-epoxipropoxi)phenyl]propane has been classified by IARC as a group 3 carcinogen.

# **SECTION 12: Ecological information**

12.1. Toxicity	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10
Product/substance	μm]
Species:	Fish
Compartment:	Freshwater
Test:	LC50
Result:	>1000 mg/L
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu$ m]
Species:	Crustacean
Compartment:	Freshwater
Test:	EC50
Result:	>1000 mg/L
Product/substance Test method: Species: Compartment: Duration: Test: Result:	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] OECD 201 Algae, Pseudokirchneriella subcapitata Freshwater 72 hours EC50 >100 mg/L
Product/substance Test method: Species: Compartment: Duration: Test: Result:	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] OECD 201 Algae, Pseudokirchneriella subcapitata Freshwater 72 hours NOEC >100 mg/L
Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	2 mg/L
Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	1.8 mg/L



Test: EC50	Product/substance Species: Duration: Test:	bis-[4-(2,3-epoxipropoxi)phenyl]propane Algae 72 hours EC50
Result: 11 mg/L		11 mg/L

Toxic to aquatic life with long lasting effects.

- 12.2. Persistence and degradability No data available.
- 12.3. Bioaccumulative potential No data available.

12.4. Mobility in soil No data available.

# 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

### 12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

# SECTION 13: Disposal considerations

# 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*) HP 4 - Irritant (skin irritation and eye damage) HP 13 - Sensitising HP 14 - Ecotoxic Dispose of contents/container to an approved waste disposal plant. Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law. EWC code 08 WASTES FROM THE MANUFACTURE. FORMULATION, SUPPLY AND USE (MESU) OF COATI

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

# SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3- epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol)	Transport hazard class: 9 Label: 9 Classification code: M6	Ш	Yes	Limited quantities: 5 L Tunnel restriction code: (-) See below for additional information.
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3- epoxipropoxi)phenyl]propane,	Transport hazard class: 9 Label: 9 Classification code: M6	III	Yes	Limited quantities: 5 l EmS: F-A S-F



	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
		Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol)				See below for additional information.
ATA	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3- epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol)	Transport hazard class: 9 Label: 9 Classification code: M6	III	Yes	See below for additional information.

# \* Packing group

\*\* Environmental hazards

# Additional information

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR/IMDG/IATA provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (ADR, IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

# SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Restrictions for application

People under the age of 18 shall not be exposed to this product.

# Demands for specific education

Use of this product requires dedicated training in work with polyurethane and epoxy products.

### SEVESO - Categories / dangerous substances

E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

### **REACH**, Annex XVII

RESION EP-MONOTint, EP-PastelTint is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 3).

# Additional information

Not applicable.

### Sources

The Management of Health and Safety at Work Regulations 1999.



### Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

# 15.2. Chemical safety assessment

No

# SECTION 16: Other information

### Full text of H-phrases as mentioned in section 3

- H315, Causes skin irritation.
- H317, May cause an allergic skin reaction.
- H319, Causes serious eye irritation.
- H411, Toxic to aquatic life with long lasting effects.
- H412, Harmful to aquatic life with long lasting effects.

# The full text of identified uses as mentioned in section 1

- LCS "C" = Consumer uses: Private households (= general public = consumers)
- LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites
- LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- SU 12 = Manufacture of plastics products, including compounding and conversion
- SU 19 = Building and construction work
- PROC 19 = Hand-mixing with intimate contact and only PPE available
- PROC 2 = Use in closed, continuous PROC ess with occasional controlled exposure
- PROC 5 = Mixing or blending in batch PROC esses for formulation of preparations and articles (multistage and/or significant contact)
- PC 32 = Polymer Preparations and Compounds
- AC 13 = Plastic articles
- ERC 3 = Formulation in materials
- ERC 5 = Industrial use resulting in inclusion into or onto a matrix
- ERC 8c = Wide dispersive indoor use resulting in inclusion into or onto a matrix
- ERC 8f = Wide dispersive outdoor use resulting in inclusion into or onto a matrix

# Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development



PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SCL = A specific concentration limit SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVBC = Unknown or variable composition, complex reaction products or of biological materials VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative

# Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law. The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

# ▼ The safety data sheet is validated by

H.A.B.

# Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en