

## SAFETY DATA SHEET

# RESION EP-MONOTint, EP-PastelTint

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Trade name**

RESION EP-MONOTint, EP-PastelTint

**Product no.**

EP901, EP903

**Unique formula identifier (UFI)**

3A50-5057-T00D-QAVN

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Filler

**Use descriptors (REACH)**

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 12	Manufacture of plastics products, including compounding and conversion
SU 19	Building and construction work
Product category	Description
PC 32	Polymer Preparations and Compounds
Process category	Description
PROC 19	Hand-mixing with intimate contact and only PPE available
PROC 2	Use in closed, continuous PROC ess with occasional controlled exposure
PROC 5	Mixing or blending in batch PROC esses for formulation of preparations and articles (multistage and/or significant contact)
Article category	Description
AC 13	Plastic articles
Environmental release category	Description
ERC 3	Formulation in materials
ERC 5	Industrial use resulting in inclusion into or onto a matrix
ERC 8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
ERC 8f	Wide dispersive outdoor use resulting in inclusion into or onto a matrix

**Uses advised against**

None known.

### 1.3. Details of the supplier of the safety data sheet

#### Company and address

##### **Polyestershoppen BV**

Oostbaan 680  
2841 ML Moordrecht  
Netherlands  
+31 85 0220090

#### Contact person

-

#### E-mail

info@polyestershoppen.nl

#### Revision

09/12/2025

#### SDS Version

4.0

#### Date of previous version

14/12/2023 (3.0)

### 1.4. ▼ Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 111 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

## SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

### 2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Eye Irrit. 2; H319, Causes serious eye irritation.

Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Hazard pictogram(s)



#### Signal word

Warning

#### Hazard statement(s)

Causes skin irritation. (H315)

May cause an allergic skin reaction. (H317)

Causes serious eye irritation. (H319)

Toxic to aquatic life with long lasting effects. (H411)

#### Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)  
Keep out of reach of children. (P102)

#### Prevention

Avoid breathing mist/vapour. (P261)  
Wash hands thoroughly after handling. (P264)  
Wear eye protection/protective gloves/protective clothing. (P280)

#### Response

IF ON SKIN: Wash with plenty of water and soap. (P302+P352)  
If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)

#### ▼ Storage

Not applicable.

#### ▼ Disposal

Dispose of contents/container in accordance with local regulation.  
(P501)

#### Hazardous substances

bis-[4-(2,3-epoxipropoxy)phenyl]propane  
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol  
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

#### Additional labelling

EUH205, Contains epoxy constituents. May produce an allergic reaction.  
EUH211, Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

UFI: 3A50-5057-T00D-QAVN

### 2.3. Other hazards

#### ▼ Additional warnings

Contains epoxy constituents. May produce an allergic reaction.  
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.  
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS No.: 1675-54-3 EC No.: 216-823-5 UK-REACH: Index No.: 603-073-00-2	25-40%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Aquatic Chronic 2, H411	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	CAS No.: 9003-36-5 EC No.: 500-006-8 UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	CAS No.: 933999-84-9 EC No.: 618-939-5 UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

## Other information

-

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

#### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

#### Burns

Not applicable.

### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs: Get medical advice/attention.

### Information to medics

Bring this safety data sheet or the label from this product.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and

nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. ▼ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Recommended storage material

Keep only in original packaging.

#### Storage conditions

Dry, cool and well ventilated

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 10(inhalable)/4(respirable)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

#### DNEL

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	0.0893 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	0.75 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	0.87 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	4.93 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Oral	0.5 mg/kg bw/day

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62.5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	104.15 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	8.7 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	29.39 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	6.25 mg/kg bw/day

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	13.6 µg/cm <sup>2</sup>
Long term – Local effects - Workers	Dermal	22.6 µg/cm <sup>2</sup>
Long term – Systemic effects - General population	Dermal	3 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	6 mg/kg bw/day
Short term – Local effects - General population	Dermal	13.6 µg/cm <sup>2</sup>
Short term – Local effects - Workers	Dermal	22.6 µg/cm <sup>2</sup>
Long term – Local effects - General population	Inhalation	270 µg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	440 µg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	5.29 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	10.57 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	5.29 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	10.57 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	1.5 mg/kg bw/day
Short term – Systemic effects - General population	Oral	1.5 mg/kg bw/day

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	28 µg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	170 µg/m <sup>3</sup>

#### PNEC

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0.006 mg/L

Freshwater sediment	Single	0.341 mg/kg
Marine water	Single	0.001 mg/L
Marine water sediment	Single	0.034 mg/kg
Sewage treatment plant	Single	10 mg/L
Soil	Single	0.065 mg/kg
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol		
<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater	Single	0.003 mg/L
Freshwater sediment		0.294 mg/kg
Intermittent release	Single	0.025 mg/L
Marine water	Single	0 mg/L
Marine water sediment	Single	0.029 mg/kg
Sewage treatment plant	Single	10 mg/L
Soil	Single	0.237 mg/kg
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)		
<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		11.5 µg/L
Freshwater sediment		283 µg/kg
Intermittent release (freshwater)		115 µg/L
Marine water		1.15 µg/L
Marine water sediment		28.3 µg/kg
Sewage treatment plant		1 mg/L
Soil		223 µg/kg

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

Take off contaminated clothing and wash it before reuse.

### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

## Individual protection measures, such as personal protective equipment

### Generally


Use only UKCA marked protective equipment.

### Respiratory Equipment

Type	Class	Colour	Standards
No special when used as intended.			


### Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn.	-	-




### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,2	> 240	EN374-2, EN16523-1, EN388



### Eye protection

Type	Standards
Safety glasses with side shields.	EN166



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Paste

#### Colour

Various colours

#### Odour / Odour threshold

Characteristic

#### pH

No data available.

#### Density (g/cm<sup>3</sup>)

1.766

#### Kinematic viscosity

No data available.

#### Particle characteristics

No data available.

#### Phase changes

##### Melting point/Freezing point (°C)

No data available.

##### Softening point/range (°C)

No data available.

- ▼ Boiling point (°C)  
No data available.
- ▼ Vapour pressure  
No data available.
- ▼ Relative vapour density  
No data available.
- ▼ Decomposition temperature (°C)  
No data available.

#### Data on fire and explosion hazards

##### Flash point (°C)

>150

- ▼ Flammability (°C)  
No data available.
- ▼ Auto-ignition temperature (°C)  
No data available.
- ▼ Lower and upper explosion limit (% v/v)  
No data available.

#### Solubility

- ▼ Solubility in water  
No data available.
- ▼ n-octanol/water coefficient (LogKow)  
No data available.
- ▼ Solubility in fat (g/L)  
No data available.

#### 9.2. Other information

##### Other physical and chemical parameters

No data available.

- ▼ Oxidizing properties  
No data available.

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

None known.

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### ▼ Acute toxicity

Product/substance  
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]  
Test method: OECD 401  
Species: Rat, male/female  
Route of exposure: Oral  
Test: LD50  
Result: >2000 mg/kg bw

Product/substance  
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]  
Test method: OECD 403  
Species: Rat, male  
Route of exposure: Inhalation  
Test: LC50 (4 hours)  
Result: >5.09 mg/L

Product/substance bis-[4-(2,3-epoxipropoxy)phenyl]propane  
Species: Rat  
Route of exposure: Oral  
Test: LD50  
Result: 15000 mg/kg

Product/substance bis-[4-(2,3-epoxipropoxy)phenyl]propane  
Species: Rabbit  
Route of exposure: Dermal  
Test: LD50  
Result: 23000 mg/kg

Product/substance Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)  
Species: Rat  
Route of exposure: Oral  
Test: LD50  
Result: 2900 mg/kg

Product/substance Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)  
Species: Rat  
Route of exposure: Dermal  
Test: LD50  
Result: >4900 mg/kg

Based on available data for the mixture, the classification criteria are not met.

### ▼ Skin corrosion/irritation

Product/substance  
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]  
Test method: OECD 404  
Species: Rabbit  
Duration: 4 hours  
Result: No adverse effect observed (Not irritating)

Causes skin irritation.

### Serious eye damage/irritation

Causes serious eye irritation.

### ▼ Respiratory sensitisation

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Test method: OECD 429  
Species: Mouse, female  
Result: No adverse effect observed (not sensitising)

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Skin sensitisation

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Test method: OECD 429  
Species: Mouse, female  
Result: No adverse effect observed (not sensitising)

May cause an allergic skin reaction.

#### ▼ Germ cell mutagenicity

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Test method: OECD 473  
Species: Mouse, Chinese Hamster Ovary (CHO)  
Conclusion: No adverse effect observed

---

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Test method: OECD 471  
Species: Bacteria, *S. typhimurium*  
Conclusion: No adverse effect observed

---

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Test method: OECD 474  
Species: Mouse, male/female  
Conclusion: No adverse effect observed

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Carcinogenicity

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Test method: OESO 453  
Species: Rat, male/female  
Route of exposure: Inhalation  
Target organ: Lung  
Duration: 24 months  
Test: NOAEC  
Result:  $5 \text{ mg/m}^3$   
Conclusion: No adverse effect observed

---

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Species: Rat, male/female  
Route of exposure: Oral  
Duration: 24 months  
Test: NOAEL  
Result: 50000 ppm  
Conclusion: No adverse effect observed

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Reproductive toxicity

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Test method: OECD 414  
 Species: Rat  
 Duration: 14 days  
 Test: NOAEL  
 Result: 1000 mg/kg bw/day  
 Conclusion: No adverse effect observed

Based on available data for the mixture, the classification criteria are not met.

#### ▼ STOT-single exposure

Based on available data for the mixture, the classification criteria are not met.

#### ▼ STOT-repeated exposure

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Aspiration hazard

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Symptoms related to the physical, chemical and toxicological characteristics

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

### 11.2. Information on other hazards

#### ▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

#### Other information

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ] has been classified by IARC as a group 2B carcinogen.  
 bis-[4-(2,3-epoxipropoxy)phenyl]propane has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Species: Fish  
 Compartment: Freshwater  
 Test: LC50  
 Result: >1000 mg/L

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Species: Crustacean  
 Compartment: Freshwater  
 Test: EC50  
 Result: >1000 mg/L

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Test method: OECD 201  
 Species: Algae, Pseudokirchneriella subcapitata  
 Compartment: Freshwater  
 Duration: 72 hours  
 Test: EC50  
 Result: >100 mg/L

Product/substance

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Test method: OECD 201  
 Species: Algae, Pseudokirchneriella subcapitata  
 Compartment: Freshwater  
 Duration: 72 hours  
 Test: NOEC  
 Result: >100 mg/L

Product/substance bis-[4-(2,3-epoxipropoxi)phenyl]propane  
 Species: Fish  
 Duration: 96 hours  
 Test: LC50  
 Result: 2 mg/L

Product/substance bis-[4-(2,3-epoxipropoxi)phenyl]propane  
 Species: Daphnia  
 Duration: 48 hours  
 Test: EC50  
 Result: 1.8 mg/L

Product/substance bis-[4-(2,3-epoxipropoxi)phenyl]propane  
 Species: Algae  
 Duration: 72 hours  
 Test: EC50  
 Result: 11 mg/L

Toxic to aquatic life with long lasting effects.

#### 12.2. [▼ Persistence and degradability](#)

Based on available data for the mixture, the classification criteria are not met.

#### 12.3. [▼ Bioaccumulative potential](#)

Based on available data for the mixture, the classification criteria are not met.

#### 12.4. [Mobility in soil](#)

No data available.

#### 12.5. [Results of PBT and vPvB assessment](#)

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

#### 12.6. [▼ Endocrine disrupting properties](#)

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

#### 12.7. [Other adverse effects](#)

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

## SECTION 13: Disposal considerations

#### 13.1. [Waste treatment methods](#)

Product is covered by the regulations on hazardous waste. (\*)

HP 4 - Irritant (skin irritation and eye damage)

HP 13 - Sensitising

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

[EWC code](#)







08

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
ADR/ADN/RID	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	Transport hazard class: 9 Label: 9 Classification code: M6  	III	Yes	Limited quantities: 5 L Tunnel restriction code: (-) See below for additional information.
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	Transport hazard class: 9 Label: 9 Classification code: M6  	III	Yes	Limited quantities: 5 L EmS: F-A S-F See below for additional information.
IATA	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	Transport hazard class: 9 Label: 9 Classification code: M6  	III	Yes	See below for additional information.

\* Packing group

\*\* Environmental hazards

#### ▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR/ADN/RID/IMDG/IATA provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (ADR, IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).

ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to

incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 shall not be exposed to this product.

#### Demands for specific education

Use of this product requires dedicated training in work with polyurethane and epoxy products.

#### SEVESO - Categories / dangerous substances

E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

#### Additional information

Not applicable.

#### Sources

The Management of Health and Safety at Work Regulations 1999.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

### 15.2. Chemical safety assessment

No

## SECTION 16: Other information

### Full text of H-phrases as mentioned in section 3

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H411, Toxic to aquatic life with long lasting effects.

H412, Harmful to aquatic life with long lasting effects.

### The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)

LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU 12 = Manufacture of plastics products, including compounding and conversion

SU 19 = Building and construction work

PROC 19 = Hand-mixing with intimate contact and only PPE available

PROC 2 = Use in closed, continuous PROC ess with occasional controlled exposure

PROC 5 = Mixing or blending in batch PROC esses for formulation of preparations and articles (multistage and/or significant contact)

PC 32 = Polymer Preparations and Compounds

AC 13 = Plastic articles  
ERC 3 = Formulation in materials  
ERC 5 = Industrial use resulting in inclusion into or onto a matrix  
ERC 8c = Wide dispersive indoor use resulting in inclusion into or onto a matrix  
ERC 8f = Wide dispersive outdoor use resulting in inclusion into or onto a matrix

#### ▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.  
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

#### The safety data sheet is validated by

H.A.B.

#### ▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en